




---

 PRODUCT-DETAILS

## AX50-30-11-80

### AX50-30-11-80 220-230V50Hz/230-240V60Hz Contactor




---

**General Information**

Extended Product Type	AX50-30-11-80
Product ID	1SBL351074R8011
EAN	3471522404800
Catalog Description	AX50-30-11-80 220-230V50Hz/230-240V60Hz Contactor
Long Description	AX50...AX80 contactors are mainly used for controlling 3-phase motors and power circuits up to 690 V AC. These contactors are of the block type design with: – 3 main poles – control circuit: AC operated – add-on auxiliary contact blocks (optional) for side mounting and a wide range of accessories.

---

**Ordering**

Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

---

**Popular Downloads**

Data Sheet, Technical Information	1SBC100187L0203
-----------------------------------	-----------------

Instructions and Manuals	9AKK107492A7059
CAD Dimensional Drawing	2CDC001079B0201

### Dimensions

Product Net Width	82 mm
Product Net Depth / Length	110 mm
Product Net Height	108 mm
Product Net Weight	1.05 kg

### Technical

Number of Main Contacts NO	3
Number of Main Contacts NC	0
Number of Auxiliary Contacts NO	1
Number of Auxiliary Contacts NC	1
Rated Operational Voltage	Auxiliary Circuit 690 V Main Circuit 690 V
Rated Frequency (f)	Auxiliary Circuit 50 / 60 Hz Main Circuit 50 / 60 Hz
Conventional Free-air Thermal Current (I <sub>th</sub> )	acc. to IEC 60947-4-1, Open Contactors $\Theta = 40\text{ °C}$ 100 A
Rated Operational Current AC-1 (I <sub>e</sub> )	(220 / 240 V) 55 °C 85 A (690 V) 40 °C 100 A (690 V) 70 °C 70 A
Rated Operational Current AC-3 (I <sub>e</sub> )	(415 V) 55 °C 50 A (440 V) 55 °C 45 A (500 V) 55 °C 45 A (690 V) 55 °C 35 A (380 / 400 V) 55 °C 50 A (220 / 230 / 240 V) 55 °C 53 A
Rated Operational Power AC-3 (P <sub>e</sub> )	(415 V) 25 kW (440 V) 25 kW (500 V) 30 kW (690 V) 30 kW (380 / 400 V) 22 kW (220 / 230 / 240 V) 15 kW
Rated Short-time Withstand Current Low Voltage (I <sub>cw</sub> )	at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 650 A at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 110 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 250 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 1000 A at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 370 A
Maximum Breaking Capacity	cos phi=0.45 (cos phi=0.35 for I <sub>e</sub> > 100 A) at 440 V 1300 A cos phi=0.45 (cos phi=0.35 for I <sub>e</sub> > 100 A) at 690 V 630 A
Rated Insulation Voltage (U <sub>i</sub> )	acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 690 V
Rated Impulse Withstand Voltage (U <sub>imp</sub> )	Auxiliary Circuit 6 kV
Maximum Electrical Switching Frequency	(AC-1) 600 cycles per hour (AC-3) 600 cycles per hour
Maximum Mechanical Switching Frequency	3600 cycles per hour
Rated Control Circuit	50 Hz 220 ... 230 V

Voltage (U <sub>c</sub> )	60 Hz 230 ... 240 V
Power Loss	at Rated Operating Conditions AC-1 per Pole 5 W at Rated Operating Conditions AC-3 per Pole 1.3 W
Operate Time	Between Coil De-energization and NC Contact Closing 7 ... 14 ms Between Coil De-energization and NO Contact Opening 4 ... 11 ms Between Coil Energization and NC Contact Opening 7 ... 22 ms Between Coil Energization and NO Contact Closing 8 ... 27 ms
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP10
Tightening Torque	Control Circuit 1 N·m Main Circuit 4 N·m
Terminal Type	Screw Terminals
Product Name	Block Contactor

## Technical UL/CSA

General Use Rating UL/CSA	(600 V AC) 80 A
Horsepower Rating UL/CSA	(120 V AC) Single Phase 3 hp (200 ... 208 V AC) Three Phase 15 hp (220 ... 240 V AC) Three Phase 20 hp (240 V AC) Single Phase 10 hp (440 ... 480 V AC) Three Phase 40 hp (550 ... 600 V AC) Three Phase 50 hp
Tightening Torque UL/CSA	Auxiliary Circuit 9 in·lb Control Circuit 9 in·lb Main Circuit 35 in·lb
Full Load Amps Motor Use	(120 V AC) Single Phase 34 A (200 ... 208 V AC) Three Phase 48.3 A (220 ... 240 V AC) Three Phase 54 A (240 V AC) Single Phase 50 A (440 ... 480 V AC) Three Phase 52 A (550 ... 600 V AC) Three Phase 52 A

## Environmental

Ambient Air Temperature	Close to Contactor Fitted with Thermal O/L Relay -25 ... 55 °C Close to Contactor without Thermal O/L Relay -40 ... 70 °C Close to Contactor for Storage -60 ... +80 °C Near Contactor for Operation in Free Air -40 ... 70 °C
Climatic Withstand	acc. to IEC 60068-2-30 and 60068-2-11 - UTE C 63-100 specification II
Maximum Operating Altitude Permissible	Without Derating 3000 m

## Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2021-006202
RoHS Information	2CMT2021-006277
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	2CMT2023-006525
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

## Certificates and Declarations

CB Certificate	9AKK107492A7074
CCC Certificate	9AKK107492A7091
CCS Certificate	GZ23PTB00147
CQC Certificate	CQC2013010304646607
Declaration of Conformity - CCC	2020980304001064
Declaration of Conformity - CE	1SBD250011U1000
UL Certificate	UL_20140702-E312527-10-7

## Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	102 mm
Package Level 1 Depth / Length	143 mm
Package Level 1 Height	152 mm
Package Level 1 Gross Weight	1.16 kg
Package Level 1 EAN	3471522404800
Package Level 2 Units	10 piece
Package Level 2 Width	240 mm
Package Level 2 Depth / Length	295 mm
Package Level 2 Height	145 mm
Package Level 2 Gross Weight	11.6 kg

## Classifications

Object Classification Code	Q
ETIM 7	EC000066 - Power contactor, AC switching
ETIM 8	EC000066 - Power contactor, AC switching
ETIM 9	EC000066 - Power contactor, AC switching
eClass	V11.0 : 27371003
UNSPSC	39121529
IDEA Granular Category Code (IGCC)	4755 >> Contactors

## Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors → AX Contactors → AX50

