



 PRODUCT-DETAILS

OT200E03CP

OT200E03CP CHANGE-OVER SWITCH



General Information

Extended Product Type	OT200E03CP
Product ID	1SCA022771R7520
EAN	6417019251912
Catalog Description	OT200E03CP CHANGE-OVER SWITCH
Long Description	200A, 3 pole manual change-over switch including a black plastic IP65 I-0-II pistol type handle (see the table below), shaft and bolt set for the cable connection. Handle padlockable in the 0-position, door interlock in the I- and II- positions and when padlocked.

Circular Value

Environmental Information	1SCC303050D0201
---------------------------	-----------------

Material Compliance

Conflict Minerals Reporting Template	9AKK108467A5658
--------------------------------------	-----------------

(CMRT)

REACH Declaration	1SCC011021D0201
RoHS Information	1SCC011020D0201
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP	882f3eb1-2d8e-4c49-9046-b2c016ad3a72 Finland (FI)
Simplified SCIP	83867940-09cc-44b8-addc-9792f1fb3986 Germany (DE) 22f05de1-9312-4851-bbfd-4c03ab58af9a Denmark (DK) 59672a61-a2ce-4d5f-a9f1-bc746e890971 Poland (PL) c97c05d3-7732-4ed6-b4a6-e9918c317475 Italy (IT) cadc8dc2-e7a9-443a-a3c9-6483337256cc France (FR) d4f1e78c-57b2-461d-b22f-051fedad1e7d Netherlands (NL) 5368b975-81e9-4889-836d-a08c61fb1c7a Portugal (PT) 9275672c-3dd8-4717-a890-6add3956be4a Spain (ES) 080cb9b3-b01b-4c86-810c-f40652096c92 Germany (DE) 4fe0b143-38e8-452e-aca5-e39a1816b022 Croatia (HR) e838298b-8297-46f8-b62a-7d9b134056df Belgium (BE) d15b368e-9754-406c-a3d8-69461b55a59f Germany (DE) dcc9412a-e682-4c7a-ab93-b0b10053d97d France (FR) 5befcb63-4466-4655-aeaf-2c663e3fc775 Germany (DE) 907b9aea-1c4e-44c6-bd4b-1a8f741656f8 Greece (GR) 89e7c28e-2833-49f0-9e93-eae46fb4ea6a Estonia (EE) 0d80ca7f-473c-4bec-a910-c8271c8f7685 Germany (DE) 5e1af34d-3e73-42d9-9cdd-c7264c1f8b71 Sweden (SE) b9f55feb-70bc-42e2-8308-b8ee5e7a2fdd Hungary (HU) 478ecef-72af-4b88-98cf-262544c1d801 Poland (PL) de059a5b-94ca-44e1-a0ca-177c20d725cd Hungary (HU) 4ea11d03-a607-4739-8aed-2ec126ce4c62 Czech Republic (CZ) 63892a83-0bfd-4f7e-ac57-669f0e7028ac Poland (PL) c6513a14-f008-48a1-a06c-388f31d24545 Bulgaria (BG) 8a7ad977-aafd-43b4-8536-bf2fb4f8a09d Belgium (BE) 95097ce5-cc65-4b5e-af34-b39b0bfe4b2b Sweden (SE) 2a0101bd-9da4-4c28-b378-e98f99ff8e5d Norway (NO)

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads

Data Sheet, Technical Information	1SCC303003C0201
Instructions and Manuals	1SCC303008M0208

Dimensions

Product Net Width	170 mm 6.69 in
Product Net Height	150 mm 5.91 in
Product Net Depth / Length	160 mm 6.3 in
Product Net Weight	3.1 kg 6.83 lb

Technical

Rated Operational	(380 ... 415 V) 200 A
-------------------	-----------------------

Current AC-21A (I_e)	(500 V) 200 A (690 V) 200 A
Rated Operational Current AC-22A (I_e)	(380 ... 415 V) 200 A (500 V) 200 A (690 V) 200 A
Rated Operational Current AC-23A (I_e)	(380 ... 415 V) 200 A (500 V) 200 A (690 V) 200 A
Rated Operational Current AC-31B (I_e)	(380 ... 415 V) 200 A
Rated Operational Current AC-33B (I_e)	(380 ... 415 V) 200 A
Rated Operational Power AC-23A (P_e)	(380 ... 415 V) 110 kW (500 V) 132 kW (690 V) 200 kW
Conventional Free-air Thermal Current (I_{th})	$\Theta = 40\text{ °C}$ 200 A
Conventional Thermal Current (I_{the})	Fully Enclosed 200 A
Rated Impulse Withstand Voltage (U_{imp})	12 kV
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Voltage	1000 V
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 1 s 8 kiloampere rms
Power Loss	4 W
Pollution Degree	3
Handle Color	Black
Handle Type	Handle and shaft included
Switches Operating Mechanism	Mechanism at the End of the Switch 03 (Left Side)
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Operating Mode	Front operated
Mounting Type	Base mounting
Number of Poles	3
Degree of Protection	Front IP20
Terminal Width	20 mm
Tightening Torque	acc. IEC 60947-1 15 ... 22 N·m
Transition Type	Open

Technical UL/CSA

Ampere Rating	200 A
Tightening Torque	acc. IEC 60947-1 15 ... 22 N·m

Environmental

Environmental Information	1SCC303050D0201
---------------------------	-----------------

Certificates and Declarations

Declaration of Conformity - CE	1SCC303001D2704
DNV Certificate	1SCC303138D0201

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	160 mm 6.3 in
Package Level 1 Depth / Length	245 mm 9.65 in
Package Level 1 Height	185 mm 7.28 in
Package Level 1 Gross Weight	3.3 kg 7.28 lb
Package Level 1 EAN	6417019251912

Classifications

Object Classification Code	Q
ETIM 8	EC000216 - Switch disconnecter
ETIM 9	EC000216 - Switch disconnecter (low voltage)
eClass	V11.1 : 27371403
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Finland)	3641503

Categories

Low Voltage Products and Systems → Switches → Change-over and Transfer Switches → Manual Change-over Switches

