



 PRODUCT-DETAILS

OT40F4N2

OT40F4N2 SWITCH-DISCONNECTOR



General Information

Extended Product Type	OT40F4N2
Product ID	1SCA104932R1001
EAN	6417019390727
Catalog Description	OT40F4N2 SWITCH-DISCONNECTOR
Long Description	4-pole, front operated, base mounted, DIN-rail mountable switch-diconnector / non-fusible disconnect switch with protected clamp terminals, handle and shaft are not included

Eco Transparency

Environmental Product Declaration - EPD	1SCC301278D0201
---	-----------------

Environmental

Environmental Information	1SCC301262D0201
---------------------------	-----------------

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	1SCC011021D0201
RoHS Information	1SCC011020D0201
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	1SCC011025D0201

Ordering

Minimum Order Quantity	10 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads

Data Sheet, Technical Information	1SCC301020C0201
Instructions and Manuals	1SCC301052M0006
Mechanical Drawings	1SCC301436F0001 1SCC301435F0001 OT16-40F4N2.igs
Environmental Product Declaration - EPD	1SCC301278D0201

Dimensions

Product Net Width	48 mm
Product Net Height	68 mm
Product Net Depth / Length	56 mm
Product Net Weight	0.125 kg

Technical

Rated Operational Current AC-21A (I_e)	(380 ... 415 V) 40 A (500 V) 40 A (690 V) 40 A
Rated Operational Current AC-22A (I_e)	(380 ... 415 V) 40 A (500 V) 40 A (690 V) 40 A
Rated Operational Current AC-23A (I_e)	(380 ... 415 V) 23 A (500 V) 23 A (690 V) 12 A
Rated Operational Power AC-23A (P_e)	(220 ... 240 V) 5.5 kW (400 ... 415 V) 11 kW (500 V) 11 kW (690 V) 11 kW
Conventional Free-air Thermal Current (I_{th})	$\Theta = 40$ °C 40 A
Conventional Thermal Current (I_{the})	Fully Enclosed 40 A

Rated Impulse Withstand Voltage (U_{imp})	8 kV
Rated Insulation Voltage (U_i)	acc. to IEC/EN 60664-1 750 V
Rated Operational Voltage	Main Circuit 750 V
Rated Short-Circuit Making Capacity (I_{cm})	(690 V) 0.71 kA
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 1 s 0.5 kA
Rated Conditional Short-Circuit Current (I_{nc})	(40 A fuse, $\leq 415V$) 50 kA (25 A fuse, 690 V) 50 kA
Power Loss	at Rated Operating Conditions per Pole 1.6 W
Pollution Degree	3
Handle Type	Knob Handle and shaft not included
Fourth Pole Position	Right Side
Fourth Pole Type	Switched - Simultaneous Function
Switches Operating Mechanism	Mechanism on Top of the Switch
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out Bottom In - Top Out
Operating Mode	Front operated
Standards	IEC 60947-3 / UL 508 / CSA C22.2 No. 14
Special Functions	No
Mounting Type	Base mounting
Number of Poles	4
Cable Cross-Section	Cu 0.75 ... 10 mm ²
Degree of Protection	Front IP20
Terminal Type	Screw Terminals
Tightening Torque	acc. IEC 60947-1 0.8 N·m
Mechanical Durability	20000
Lock Type	No

Technical UL/CSA

Maximum Operating Voltage UL/CSA	600 V
Ampere Rating	40 A
Horsepower Rating UL/CSA	(110 ... 120 V AC) Single Phase 2 Hp (240 V AC) Single Phase 5 Hp (440 ... 480 V AC) Single Phase 10 Hp (550 ... 600 V AC) Single Phase 15 Hp (220 ... 240 V AC) Three Phase 10 Hp (440 ... 480 V AC) Three Phase 20 Hp (550 ... 600 V AC) Three Phase 25 Hp
Tightening Torque	acc. IEC 60947-1 0.8 N·m
Tightening Torque UL/CSA	7 in·lb

Certificates and Declarations

A2L Certificate – IEC	1SCC301335D0201
ATEX Certificate	No certification needed

Declaration of Conformity - CE	1SCC301166D2703
UL Certificate	cULus certificate OT16-80
VDE Certificate	No certification needed

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	67 mm
Package Level 1 Depth / Length	79 mm
Package Level 1 Height	61 mm
Package Level 1 Gross Weight	0.14 kg
Package Level 1 EAN	6417019390727

Classifications

Object Classification Code	Q
ETIM 8	EC000216 - Switch disconnecter
ETIM 9	EC000216 - Switch disconnecter (low voltage)
UNSPSC	39122233
IDEA Granular Category Code (IGCC)	5290 >> Disconnect switch
eClass	V11.1 : 27371403
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Finland)	3601442
E-Number (Sweden)	3171069

Categories

Low Voltage Products and Systems → Switches → Switch Disconnectors

