




PRODUCT-DETAILS

OTM2000E3CM230C

OTM2000E3CM230C MOTORIZED C/O SWITCH



General Information	
Extended Product Type	OTM2000E3CM230C
Product ID	1SCA112709R1001
EAN	6417019454054
Catalog Description	OTM2000E3CM230C MOTORIZED C/O SWITCH
Long Description	OTM2000E3CM230C MOTORIZED C/O SWITCH, Direct mounted handle, Open transition

Circular Value	
End of Life Instructions	1SCC303061M0201
Environmental Information	1SCC303036D0202

Material Compliance	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658

REACH Declaration	1SCC011021D0201
RoHS Information	1SCC011020D0201
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads

Data Sheet, Technical Information	1SCC303003C0201
Instructions and Manuals	1SCC303002M0204
End of Life Instructions	1SCC303061M0201

Dimensions

Product Net Width	645 mm
Product Net Height	377 mm
Product Net Depth / Length	335 mm
Product Net Weight	645 lb 78 kg

Technical

Rated Operational Current AC-21B (I_e)	(380 ... 415 V) 2000 A (500 V) 2000 A
Conventional Free-air Thermal Current (I_{th})	$\Theta = 40^\circ\text{C}$ 2000 A
Rated Impulse Withstand Voltage (U_{imp})	12 kV
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Voltage	1000 V
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 1 s 55 kiloampere rms
Motor Operational Voltage	220 ... 240 V AC
Power Loss	55 W
Pollution Degree	3
Handle Color	Black
Handle Type	Direct mounted handle
Switches Operating Mechanism	Mechanism at the End of the Switch
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Operating Mode	Front operated

Mounting Type	Base mounting
Number of Poles	3
Degree of Protection	Front IP20
Transition Type	Open

Environmental

Environmental Information	1SCC303036D0202
---------------------------	-----------------

Certificates and Declarations

Declaration of Conformity - CE	1SCC303028D0201
--------------------------------	-----------------

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	580 mm
Package Level 1 Depth / Length	780 mm
Package Level 1 Height	500 mm
Package Level 1 Gross Weight	78 kg
Package Level 1 EAN	6417019454054

Classifications

Object Classification Code	Q
ETIM 8	EC000216 - Switch disconnecter
ETIM 9	EC000216 - Switch disconnecter (low voltage)
eClass	V11.1 : 27371403
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)
E-Number (Finland)	3641796

Categories

Low Voltage Products and Systems → Switches → Change-over and Transfer Switches → Motorized Change-over Switches

