



PRODUCT-DETAILS

XT5S 630 Ekip Dip LS/I In=630 3p F F

XT5S 630 Ekip Dip LS/I In=630 3p F F



General Information	
Extended Product Type	XT5S 630 Ekip Dip LS/I In=630 3p F F
Product ID	1SDA100425R1
EAN	8056221005029
Catalog Description	XT5S 630 Ekip Dip LS/I In=630 3p F F
Long Description	C.BREAKER TMAX XT5S 630 FIXED THREE-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC EKIP DIP LS/I R 630

ABB EcoSolutions	
ABB EcoSolutions	Yes

Circular Value	
Circular Design Principles Recyclability Rate	Design for Closing Resource Loops - Standard EN45555 - 59.6 %
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
End of Life Instructions	9AKK108468A2354

Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available
Toxic Substances Control Act - TSCA	9AKK108467A8326

Eco Transparency

Environmental Product Declaration - EPD	9AKK108468A1899 9AKK108468A9748
---	------------------------------------

Environmental

Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP	6091f05c-5419-4062-a103-b02f5313f28e Italy (IT)
Simplified SCIP	7b36fa72-12a9-41e6-aceb-79afa009ee0b Germany (DE) 8391e5fc-e139-4403-b804-0f65fb0a8b20 Hungary (HU) 1ffaf2e4-5a52-488c-b564-6d1332999bbd France (FR) 29841818-9325-42e4-84a7-bab9b51e7aa3 Portugal (PT) 70fd07da-e995-42d9-8c81-cefe2ec233ac France (FR) 7939744b-3d59-4716-9fd2-8399a6d1e6a7 Germany (DE) 67c760f1-6a30-4972-adde-4d6e831de9e6 Germany (DE) 7f94add5-343f-4511-9777-d86549a79962 Sweden (SE) ad6f5093-7c71-4716-a4cf-057eca64131a Croatia (HR) bfc2b2a9-d2f8-44bf-8e94-e50c49bde6e5 Czech Republic (CZ) 315a4a68-b1fa-4b20-a57b-83e56813c200 Belgium (BE) 5ce95a22-0c28-485f-9e05-e3d834d92e3a Germany (DE) 18702780-f581-4518-b143-1fa9e495e505 Sweden (SE) a7abd755-9a14-4f45-a342-8aebbd36cc38 Bulgaria (BG) 53a75bfd-d2b6-49f5-9c8c-4cc239d5e88c Greece (GR) 7acc8940-9b71-497d-9a24-708c329badc1 Estonia (EE) 1af57ed4-8303-4411-91cf-7ae738914102 Hungary (HU) e3446c7d-fb14-4cd0-a196-1bd744c6577c Spain (ES) 23289ffb-cc8d-469f-9e22-a841f47b085e Netherlands (NL) ed11dbf2-6e2a-4a96-a351-2656fa60c251 Poland (PL) ef66c90d-0bd5-4dad-a750-18d17b9f9610 Belgium (BE) 4ae62a60-d361-4657-8df1-802b306c098b Germany (DE) 44a33acc-42eb-4820-8a0e-d96fcd2eb42f Poland (PL) c5411e8c-0047-4872-a490-67783140539d Denmark (DK) 188260c2-ea79-4894-9895-f846e575e874 Poland (PL) c58c2c97-ceed-48b8-94e1-bf0ec13a0d30 Norway (NO) c82c0f8e-471c-40c0-a52d-40d44d1201c1 Finland (FI)

Ordering

Order Code US and Canada	XT5SE363BEFF000XXX
E-Number (Finland)	3641346
EAN	8056221005029
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	140 mm
Product Net Height	205 mm
Product Net Depth / Length	103.5 mm
Product Net Weight	4.82 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	250 mm
Package Level 1 Height	245 mm
Package Level 1 Depth / Length	285 mm
Package Level 1 Gross Weight	5.308 kg
Package Level 1 EAN	8056221005029

Additional Information

Circuit Breaker Type to be Associated	Power Distribution
Current Type	AC
Electrical Durability	120 cycles per hour 5000 cycle
Mechanical Durability	240 cycles per hour 20000 cycle
Number of Poles	3
Order Multiple	1 piece
Power Loss	45 W
Product Main Type	SACE Tmax XT
Product Name	Moulded Case Circuit Breaker
Product Type	Automatic Circuit Breaker
Rated Current (I_n)	630 A
Rated Impulse Withstand Voltage (U_{imp})	8 kV
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Voltage	690 V AC
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(220 V AC) 85 kA (230 V AC) 85 kA (240 V AC) 85 kA (380 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 30 kA (525 V AC) 30 kA (690 V AC) 25 kA
Rated Short-time Withstand Current Low Voltage (I_{cwl})	6 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	(220 V AC) 85 kA (230 V AC) 85 kA (240 V AC) 85 kA (380 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 30 kA (525 V AC) 30 kA (690 V AC) 25 kA
Rated Uninterrupted Current (I_u)	630 A
Release	Ekip Dip LS/I
Release Type	EL
Short-Circuit Performance Level	S
Standards	IEC60947-2
Sub-type	XT5
Terminal Connection Type	Front
Version	F
CAD Dimensional Drawing	1SDH002065A1115 1SDH002065A1131

Certificates and Declarations

Data Sheet, Technical Information	1SDC210100D0206 1SDC210099D0206
Declaration of Conformity - CE	9AKK107680A2824
Mechanical Drawings	1SDH002011A1101
Wiring Diagram	1SDM000005A1001
Instructions and Manuals	1SDH002011A1001

Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

