



PRODUCT-DETAILS

AX205-30-11-84

AX205-30-11-84 Contactor



General Information	
Extended Product Type	AX205-30-11-84
Product ID	1SFL501074R8411
EAN	7320500500316
Catalog Description	AX205-30-11-84 Contactor
Long Description	AX205-30-11-84 Contactor

Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

Popular Downloads	
Data Sheet, Technical Information	1SBC100214C0202
Instructions and Manuals	9AKK107492A7061
CAD Dimensional	2CDC001079B0201

Drawing

Dimensions	
Product Net Width	111.5 mm
Product Net Depth / Length	162.3 mm
Product Net Height	196 mm
Product Net Weight	3.2 kg

Technical	
Number of Main Contacts NO	3
Number of Main Contacts NC	0
Number of Auxiliary Contacts NO	1
Number of Auxiliary Contacts NC	1
Number of Poles	3P
Rated Operational Voltage	Main Circuit 1000 V
Rated Frequency (f)	Main Circuit 60 Hz
Conventional Free-air Thermal Current (I _{th})	acc. to IEC 60947-4-1, Open Contactors Θ = 40 °C 250 A
Rated Operational Current AC-1 (I _e)	(690 V) 40 °C 275 A (690 V) 55 °C 250 A (690 V) 70 °C 180 A
Rated Operational Current AC-3 (I _e)	(415 V) 55 °C 205 A (440 V) 55 °C 185 A (500 V) 55 °C 170 A (690 V) 55 °C 170 A (380 / 400 V) 55 °C 205 A (220 / 230 / 240 V) 55 °C 205 A
Rated Operational Power AC-3 (P _e)	(415 V) 110 kW (440 V) 90 kW (500 V) 110 kW (690 V) 132 kW (380 / 400 V) 110 kW (220 / 230 / 240 V) 59 kW
Rated Breaking Capacity AC-3	8 x I _e AC-3
Rated Making Capacity AC-3	10 x I _e AC-3
Rated Short-time Withstand Current Low Voltage (I _{cw})	at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 1200 A at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 280 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 600 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 1800 A at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 800 A
Rated Insulation Voltage (U _i)	acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 690 V
Rated Impulse Withstand Voltage (U _{imp})	8 kV
Maximum Electrical Switching Frequency	300 cycles per hour
Mechanical Durability	5 million
Maximum Mechanical Switching Frequency	3600 cycles per hour

Coil Operating Limits	(acc. to IEC 60947-4-1) Uc (at $\theta \leq 70\text{ }^{\circ}\text{C}$)
Rated Control Circuit Voltage (Uc)	50 Hz 110 V 60 Hz 110 ... 120 V
Power Loss	at Rated Operating Conditions per Pole 5 W
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP40
Terminal Type	Main Circuit: Bars
Product Name	Block Contactor

Environmental

Ambient Air Temperature	Close to Contactor Fitted with Thermal O/L Relay (0.85 ... 1.1 Uc) -25 ... 55 °C Close to Contactor without Thermal O/L Relay (0.85 ... 1.1 Uc) -40 ... 70 °C Close to Contactor for Storage -40 ... 70 °C
Maximum Operating Altitude Permissible	Without Derating 3000 m

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2021-006202
RoHS Information	2CMT2021-006277
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	2CMT2023-006525
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations

CQC Certificate	CQC2013010304646598
Declaration of Conformity - CCC	2020980304001070
Declaration of Conformity - CE	2CMT2015-005443
UL Certificate	20160920-E36588

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	180 mm
Package Level 1 Depth / Length	245 mm
Package Level 1 Height	175 mm
Package Level 1 Gross Weight	3.8 kg
Package Level 1 EAN	7320500500316

Classifications

Object Classification Code	Q
----------------------------	---

ETIM 7	EC000066 - Power contactor, AC switching
ETIM 8	EC000066 - Power contactor, AC switching
ETIM 9	EC000066 - Power contactor, AC switching
eClass	V11.0 : 27371003
UNSPSC	39121529
IDEA Granular Category Code (IGCC)	4755 >> Contactors

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors → AX Contactors → AX205

