

PRODUCT-DETAILS

CR-M110DC3L

CR-M110DC3L Pluggable interface relay 3c/o, A1-A2=110VDC, 250V/10A, LED



General Information	
Extended Product Type	CR-M110DC3L
Product ID	1SVR405612R8100
EAN	4013614497643
Catalog Description	CR-M110DC3L Pluggable interface relay 3c/o, A1-A2=110VDC, 250V/10A, LED
Long Description	The CR-M110DC3L pluggable interface relay is a miniature relay, which is to be plugged into a suitable ABB CR-M socket. Plugged into a socket, the combination of relay and socket may be seemlessly snap-on mounted onto a DIN Rail. This relay operates with a 110 V DC rated control supply voltage and has a 3 c/o (SPDT) output with contacts rated at 250 V / 10 A, enabling the possibility of switching multiple circuits with a single input signal. The relay has an integrated test button which is used for the manual actuation of the relay by locking it's output contacts. The test button facilitates easy testing and commissioning. The relay also has an integrated LED, which provides the visual indication of the energization of the relay coil. Standard sockets, logic sockets, pluggable function modules, holders and markers are available as accessories. Standard sockets, logical sockets, pluggable function modules, holder

Ordering	
EAN	

4013614497643

2024/11/22

Subject to change without notice

© 2024 ABB. All rights reserved.

Minimum Order Quantity	10 piece
Customs Tariff Number	85364900

Popular Downloads	
Data Sheet, Technical Information	2CDC110004C0210_05
Instructions and Manuals	1SVC405600M9000
CAD Dimensional Drawing	2CDC001079B0201

21.2 mm
35.6 mm
27.5 mm
0.033 kg

Technical	
Function	Pluggable miniature interface relay CR-M
Sub-Function	Relay with built in LED
Rated Control Supply Voltage (U_s)	110 V DC
Rated Operational Voltage	250 V AC
Output	3 c/o (SPDT) contacts
Output Signal	250 V / 10 A
Terminal Type	Flat-Pin Connections
Rated Operational Current AC-12 (I _e)	(230 V) 10 A
Rated Operational	(120 V) 3 A
Current AC-15 (I _e)	(230 V) 1.5 A
Rated Operational Current DC-12 (I _e)	(24 V) 10 A
Rated Operational	(24 V) 2.5 A
Current DC-13 (I _e)	(250 V) 0.1 A
Rated Insulation Voltage (Ui)	250 V
Degree of Protection	IP40
Mounting Position	1
Standards	CAN/CSA C22.2 No.14
	IEC/EN 63000
	IEC/EN 61810-1
	UL 508

Technical UL/CSA	
Maximum Operating Voltage UL/CSA	300 V AC
Contact Rating UL/CSA	B300
Pilot Duty UL/CSA	B300
Flammability According to UL94	НВ

© 2024 ABB. All rights reserved.

Environmental		
Ambient Air		Operation -40 +70 °C
Temperature		Storage -40 +85 °C
Maximum Operating Altitude Permissible		Without Derating 2000 m
Material Compliance		
Conflict Minerals Reporting Template (CMRT)		9AKK108467A5658
RoHS Information		1SVD982021-0003
RoHS Status		Following EU Directive 2011/65/EU
Certificates and Declarations		
CCC Certificate		CCC_2014010303720193
CQC Certificate		CQC2014010303720193
CSA Certificate		CSA_2735700
cUR Certificate		cUR_E244330
Declaration of Conformity - CCC		2020980303000200
Declaration of Conformity - CE		1SVD982021-0003
Declaration of Conformity - UKCA		1SVD982021-1000
EAC Certificate		EAC_RU_C-DE.ME77.B.00446-19
RMRS Certificate		RMRS_1740019250
UR Certificate VDE Certificate		UR_E244330 VDE_40040327
Container Information		
Package Level 1 Units		box 10 piece
Package Level 1 Width		114 mm
Package Level 1 Depth / Length		50 mm
Package Level 1 Height		61 mm
Package Level 1 Gross Weight		0.35 kg
Package Level 1 EAN		4013614373459
Classifications		
Object Classification Code		к
ETIM 7		EC001437 - Switching relay
ETIM 8		EC001437 - Switching relay
ЕТІМ 9		EC001437 - Switching relay
eClass		V11.0 : 27371601
UNSPSC		39122331
E-Number (Finland)		2712687
© 2024 APP All rights received	2024/11/22	Cubicat to abone

© 2024 ABB. All rights reserved.

Subject to change without notice

Categories

Low Voltage Products and Systems \rightarrow Control Products \rightarrow Electronic Relays and Controls \rightarrow Interface Relays and Optocouplers Medium Voltage Products and Systems \rightarrow Service \rightarrow Spares and Consumables \rightarrow Parts \rightarrow All Spare Parts (Relays-SWG-CB) Medium Voltage Products and Systems \rightarrow Switchgear and Motor Control \rightarrow IEC - Primary Air Insulated Switchgear \rightarrow UniGear \rightarrow UniGear ZS2

