

# Product datasheet

Specifications



## voltage release MX - 24 V DC/AC 50/60Hz

33810

### Main

Range	MasterPacT
Range Of Product	MasterPact NT ComPacT NS630b...1600 new generation
Device Short Name	MX
Product Or Component Type	Voltage release
Device Application	Control
Voltage Release Type	Opening coil Instantaneous voltage release
Control Type	Standard
[Uc] Control Circuit Voltage	24 V AC 50/60 Hz 24...30 V DC
Circuit Breaker Mounting Mode	Drawout
Range Compatibility	Masterpact MasterPact NT ComPact ComPact NS630b...1600

### Complementary

Operating Threshold	0.7...1.1 x Un opening
Response Time	50 ms +/- 10 % for MasterPact NT 50 ms +/- 10 % for Compact NS630b...1600
Supply Holding Power	4.5 VA

### Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.4 cm
Package 1 Width	6.1 cm
Package 1 Length	8.3 cm
Package 1 Weight	2.023 kg

### Contractual warranty

Warranty	18 months
----------	-----------

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

Mercury Free

Rohs Exemption Information Yes

## Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Pro-active compliance (Product out of EU RoHS legal scope)

China Rohs Regulation [China RoHS declaration](#)  
Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)