# **Product datasheet**

Specifications





# voltage release MX - 380..480 V AC 50/60Hz

33815

### Main

Range	MasterPacT
Range Of Produc	MasterPact NT ComPacT NS630b1600 new generation
Device Short Name	MX
Product Or Component Type	Voltage release
Device Application	Control
Voltage Release Type	Opening coil Instantaneous voltage release
Control Type	Standard
[Uc] Control Circuit Voltage	380480 V AC 50/60 Hz
Circuit Breaker Mounting Mode	Drawout
Range Compatibility	Masterpact MasterPact NT ComPact ComPact NS630b1600

## Complementary

Operating Threshold	0.71.1 x Un opening
Response Time	50 ms +/- 10 % for MasterPact NT 50 ms +/- 10 % for Compact NS630b1600
Supply Holding Power	4.5 VA

## **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.5 cm
Package 1 Width	6.1 cm
Package 1 Length	8.3 cm
Package 1 Weight	1.165 kg

## **Contractual warranty**

Warranty 18 months

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance



Mercury Free



Rohs Exemption Information

Yes

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information