

Product datasheet

Specifications



auxiliary contact - ready..close NO/
NC 5 A240 V - Masterpact NW -
drawout

48469

Main

Product Or Component Type	Auxiliary contact
Device Short Name	PF
Range Compatibility	Masterpact MasterPact NW
Signal Contacts Composition	1 NO/NC

Complementary

Auxiliary Contacts Type	Standard
Mounting Mode	Drawout
Breaking Capacity (A)	AC-12: 5 A at 480 V AC 50/60 Hz AC-12: 3 A at 690 V AC 50/60 Hz AC-12: 5 A at 240/380 V AC 50/60 Hz DC-12: 0.15 A at 250 V DC DC-12: 3 A at 24/48 V DC DC-12: 0.3 A at 125 V DC
Minimum Load	100 mA at 24 V

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	1.0 cm
Package 1 Width	4.7 cm
Package 1 Length	15.0 cm
Package 1 Weight	42.0 g

Contractual warranty

Warranty	18 months
----------	-----------

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Sustainability


Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.


Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

Well-being performance

 Mercury Free

 Rohs Exemption Information [Yes](#)

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information
