

# Product datasheet

Specifications



## Acti9 IHP 2C w (24h/7d) programmable time switch

CCT15443

**Price: 219,170.46 NGN**

### Main

range of product	Acti9
Product name	Acti9 IHP
Device short name	IHP
Product or component type	Programmable digital time switch
Device application	Building
Number of channels	2
User language	English French German Dutch Italian Spanish Portuguese Danish Norwegian Swedish Finnish
Colour tint	White

### Complementary

Load type	incandescent lamp: 2600 W halogen lamp: 2600 W non-corrected fluorescent tube: 2600 VA serial-compensated fluorescent tube: 2600 VA parallel compensated fluorescent lamp: 400 VA (48 $\mu$ F) compact fluorescent lamp: 400 W < 2 W LED lamp: 25 W > 2 W LED lamp: 200 W
Maximum power consumption in W	0.5 W standby
Maximum switching current	10 A - 250 V AC pf = 0.6 16 A - 250 V AC pf = 1
Minimum switching current	10 mA 230 V AC 100 mA 24 V AC/DC
[Ue] rated operational voltage	230 V AC +10 % -15 % at 50/60 Hz
Electrical insulation class	Class II
Output type	Dry contact
Accuracy	+/- 0.25 s/day 25 °C
contacts type	C/O
Cycle duration	24 hours + 7 days
Maximum number of switchings	56

<b>Minimum interval duration</b>	1 min
<b>Function available</b>	Code lock function Holiday schedules Automatic winter/summer time changeover On/off permanent switching Manual operation On/off switching times Switch preselection
<b>Control button type</b>	4 push-buttons
<b>Backup time</b>	10 years time and program saving
<b>Type of setting</b>	Weekly programming
<b>Connections - terminals</b>	2 x 0.5...2.5 mm <sup>2</sup> screw terminals solid or flexible 1 x 2.5 mm <sup>2</sup> screw terminals solid or flexible with sleeve
<b>Mounting support</b>	TH35 DIN rail conforming to EN 60715
<b>Width</b>	45 mm
<b>Height</b>	92.6 mm
<b>Depth</b>	66.7 mm
<b>Net weight</b>	130 g
<b>Marking</b>	CE
<b>Overvoltage category</b>	Class 3
<b>Function</b>	None
<b>Absence for holidays</b>	Yes
<b>Time changeover</b>	Automatic
<b>Updated by</b>	None

## Environment

<b>Standards</b>	EN 60730-2-7:2010
<b>Ambient air temperature for operation</b>	-30...55 °C
<b>ambient air temp for storage/ transportation</b>	-30...70 °C
<b>Relative humidity</b>	90 %, non-condensing
<b>IP degree of protection</b>	IP20

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	6.500 cm
<b>Package 1 Width</b>	8.000 cm
<b>Package 1 Length</b>	10.200 cm
<b>Package 1 Weight</b>	174.000 g
<b>Unit Type of Package 2</b>	S03
<b>Number of Units in Package 2</b>	40
<b>Package 2 Height</b>	30.000 cm
<b>Package 2 Width</b>	30.000 cm
<b>Package 2 Length</b>	40.000 cm

---

Package 2 Weight

7.422 kg

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[How this information helps you >](#)

### Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard **No**

Packaging without single use plastic **No**

EU RoHS Directive **Compliant with Exemptions**

SCIP Number **7267ef83-877b-4767-8e69-8d32bf47494a**

REACH Regulation [REACH Declaration](#)

China RoHS Regulation [China RoHS declaration](#)

## Use Again

### Repack and remanufacture

Circularity Profile [End of Life Information](#)

Removable battery **No**

WEEE



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

---

Take-back

No

---

Image of product / Alternate images

Alternative

---

