

AvatarOn, socket-outlet, 16A, 2P + 3P, wine gold

E83426TS_WG

Main

Product or component type	Socket-outlet
Device presentation	Complete product
Device application	Power supply
Load type	No inductive load
Colour tint	Wine gold
Outlet poles configuration	2P + 3P
Outlet standard deviation	British BS 1363A

Complementary

,		
Rated current	16 A at 250 V AC 50 Hz	
Socket number	2	
Socket-outlet type	Shuttered	
Clamping connection capacity	1 x 42 x 4 mm² for solid cable(s) 1 x 42 x 4 mm² for stranded cable(s) 1 x 2.53 x 2.5 mm² for solid cable(s) 1 x 2.53 x 2.5 mm² for stranded cable(s)	
Connections - terminals	Folded terminal	
Material	Polycarbonate grid plate Polycarbonate surround	
Device mounting	Surface	
Width	86 mm	
Height	86 mm	
Depth	27.5 mm	

Environment

IP degree of protection	IP20
Maximum ambient air temperature for operation	45 °C
Ambient air temperature for storage	-560 °C
Relative humidity	095 %
Environmental characteristic	UV resistant
Standards	IEC 60884

Packing Units

Unit Type of Package 1 PCE

List Price displayed is VAT EXCLUSIVE.

Number of Units in Package 1	1
Package 1 Height	4.5 cm
Package 1 Width	8.5 cm
Package 1 Length	8.5 cm
Package 1 Weight	100.0 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	9.5 cm
Package 2 Width	15 cm
Package 2 Length	19 cm
Package 2 Weight	1 kg
Unit Type of Package 3	CAR
Number of Units in Package 3	60
Package 3 Height	21 cm
Package 3 Width	30 cm
Package 3 Length	39.5 cm
Package 3 Weight	6 kg
SCC14	23606481455147



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

⊘ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	12
Environmental Disclosure	Product Environmental Profile

Use Better

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration
China RoHS Regulation	China RoHS declaration

Use Again

○ Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No

Image of product / Alternate images

Alternative

