

# Product datasheet

Specifications



Manual transfer switch, GoPact MTS 1000, 4 poles, 630A, 415VAC 50/60Hz, extended rotary handle, open transition

GM1AD4N6304BEE

## Main

Range of product	GoPact MTS
Product or component type	Manual transfer switch
Product name	GoPact MTS 1000
Device application	Change source of supply
frame size	1000
Suitability for isolation	Yes conforming to IEC 60947-3
transfer switch class	PC
poles description	4P
[Ie] rated operational current	AC-21A: 630 A conforming to IEC 60947-3 AC-22A: 630 A conforming to IEC 60947-3 AC-23A: 630 A conforming to IEC 60947-3
[Ith] conventional free air thermal current	630 A at 40 °C
[Ithe] conventional enclosed thermal current	630 A (40 °C)
Rated operational power in W	315 kW AC-23A conforming to IEC 60947-3
[Ue] rated operational voltage	415 V AC 50/60 Hz
Breaking capacity	5040 A AC-23A
Rated making capacity	6300 A AC-23A
Control type	Extended rotary handle
Operating mode	Manual
Contact position indicator	Yes
mechanical interlocking	With mechanical interlocking
Locking options description	Padlocking in OFF position 1 to 3 padlocks

## Complementary

[Ui] rated insulation voltage	1000 V AC
[Uimp] rated impulse withstand voltage	12 kV
[Icm] rated short-circuit making capacity	73.5 kA peak
[Icw] rated short-time withstand current	35 kA during 1 s conforming to IEC 60947-4-3 70 kA during 0.2 s conforming to IEC 60947-4-3
Number of contact position	3
mounting mode	Fixed
mounting support	Backplate

<b>Connections - terminals</b>	2 cable with lug wire size 400 mm <sup>2</sup>
<b>Tightening torque</b>	35 N.m
<b>Mechanical durability</b>	10000 cycles
<b>Electrical durability</b>	1000 cycles 415 V
<b>Width</b>	380 mm
<b>Height</b>	351.6 mm
<b>Depth</b>	Without handle : 210 mm With handle : 360 mm
<b>Net weight</b>	20 kg
<b>Standards</b>	IEC 60947-3
<b>Product certifications</b>	IECEE CB Scheme

## Environment

<b>Electrical shock protection class</b>	Class II
<b>IP degree of protection</b>	IP54 front face conforming to IEC 60529
<b>Pollution degree</b>	3 conforming to IEC 60664-1
<b>Ambient air temperature for operation</b>	-5...55 °C
<b>Temperature derating table</b>	40 °C ( 630 A ) 45 °C ( 630 A ) 50 °C ( 630 A ) 55 °C ( 598 A )
<b>Ambient air temperature for storage</b>	-25...85 °C
<b>Operating altitude</b>	2000 m 100 % of In 3000 m 96 % of In 4000 m 93 % of In 5000 m 89 % of In

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	46 cm
<b>Package 1 Width</b>	41 cm
<b>Package 1 Length</b>	46.5 cm
<b>Package 1 Weight</b>	34.1 kg

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)


[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

 Mercury Free

 Rohs Exemption Information Yes

 Pvc Free

## Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)  
Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure [Product Environmental Profile](#)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Circularity Profile [End of Life Information](#)