

Bảng thông số sản phẩm

Thông số kỹ thuật



Motor circuit breaker, TeSys GV5, 3P, 220A, Icu 36kA, thermal magnetic

GV5P220F

Main

Range of product	TeSys GV5
Range	TeSys
Device short name	GV5P
Product name	TeSys GV5 TeSys Giga
Product or component type	Motor circuit breaker
Device application	Motor protection
Trip unit technology	Electronic

Complementary

Poles description	3P
Utilisation category	Category A conforming to IEC 60947-2
Motor power kW	90...110 kW at 400/415 V AC 50/60 Hz 110 kW at 500 V AC 50/60 Hz 110...132 kW at 660/690 V AC 50/60 Hz
Breaking capacity	36 kA Icu at 400/415 V AC 50/60 Hz conforming to IEC 60947-2 30 kA Icu at 500 V AC 50/60 Hz conforming to IEC 60947-2 8 kA Icu at 660/690 V AC 50/60 Hz conforming to IEC 60947-2
[Ics] rated service short-circuit breaking capacity	100 % at 400/415 V AC 50/60 Hz conforming to IEC 60947-2 100 % at 500 V AC 50/60 Hz conforming to IEC 60947-2 100 % at 660/690 V AC 50/60 Hz conforming to IEC 60947-2
Control type	Direct rotary handle
[In] rated current	220 A at 65 °C
Magnetic tripping current	3300 A
[Ue] rated operational voltage	690 V AC 50/60 Hz
[Ui] rated insulation voltage	800 V AC 50/60 Hz conforming to IEC 60947-2
[Ith] conventional free air thermal current	220 A conforming to IEC 60947-4-1
[Uimp] rated impulse withstand voltage	8 kV
Power dissipation per pole	17.6 W
Mechanical durability	20000 cycles
Electrical durability	10000 cycles for AC-3 at 400/415 V In
Maximum operating rate	25 cyc/h
Rated duty	Continuous
Connection pitch	35 mm without spreaders

Connections - terminals	Bars Lugs
Tightening torque	15 N.m M8 screw type
Mechanical robustness	Vibrations: +/- 1 mm 2...13.2 Hz conforming to IEC 60068-2-6 Vibrations: 0.7 gn 13.2...100 Hz conforming to IEC 60068-2-6
Phase failure sensitivity	Yes conforming to IEC 60947-4-1
Height	161 mm
Width	105 mm
Depth	155 mm
Net weight	2.6 kg
Colour	Anthracite (RAL 7016)
Suitability for isolation	Yes conforming to EN/IEC 60947-2

Environment

Standards	EN/IEC 60947-1 EN/IEC 60947-2 EN/IEC 60947-4-1 UL 60947-4-1 CSA C22.2 No 60947-4-1
Product certifications	IECEE CB Scheme EAC (pending)
Climatic withstand	conforming to IACS E10
IK degree of protection	IK07 conforming to IEC 62262
IP degree of protection	IP40 conforming to IEC 60529
Ambient air temperature for storage	-50...85 °C
Fire resistance	960 °C conforming to IEC 60695-2-11
Operating altitude	5000 m
Ambient air temperature for operation	-25...70 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	18.2 cm
Package 1 Width	11.1 cm
Package 1 Length	17.8 cm
Package 1 Weight	2.194 kg
Unit Type of Package 2	S04
Number of Units in Package 2	6
Package 2 Height	30.0 cm
Package 2 Width	40.0 cm
Package 2 Length	60.0 cm
Package 2 Weight	14.03 kg

Contractual warranty

Warranty	18 months
-----------------	-----------

Environmental Data

Schneider Electric nhắm đến việc đạt được vị trí Net Zero vào năm 2050 thông qua các quan hệ đối tác chuỗi cung ứng, giảm vật liệu tác động và sự tuần hoàn thông qua chiến dịch "Use Better, Use Longer, Use Again" đang diễn ra của chúng tôi để kéo dài tuổi thọ sản phẩm và khả năng tái chế.

[Dữ liệu môi trường đã giải thích >](#)

[Cách chúng tôi đánh giá tính bền vững của sản phẩm >](#)

Ảnh hưởng môi trường

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	1188
-------------------------------------------------------	-------------

Environmental Disclosure	Product Environmental Profile
--------------------------	-----------------------------------------------

Use Better

Vật liệu và Bao bì

Packaging made with recycled cardboard	No
----------------------------------------	-----------

Packaging without single use plastic	No
--------------------------------------	-----------

EU RoHS Directive	Compliant with Exemptions
-------------------	----------------------------------

SCIP Number	B82c98c5-1228-42d6-959b-58bfb6c14066
-------------	---------------------------------------------

REACH Regulation	REACH Declaration
------------------	-----------------------------------

China RoHS Regulation	China RoHS declaration
-----------------------	----------------------------------------

Use Again

Đóng gói lại và tái sản xuất

Circularity Profile	End of Life Information
---------------------	-----------------------------------------

WEEE



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Take-back

No

Offer Marketing Illustration

Product benefits / Features

TeSys Giga Motor Circuit Breakers



Reliable

Highly reliable because of thermal elements including automatic compensation for changes in temperature.



Advanced technology

A brilliant alliance of advanced electronics and electromechanical technology that provides more effective protection.



East to install

Thanks to universal fixing arrangement and wide range of accessories and auxiliaries.



Offer Marketing Illustration

Product benefits / Features



TeSys Giga Motor Circuit Breakers

Technical Benefits



2 breaking capacities (Icu): 36kA & 70kA @ 400/415V AC and 4 current ratings: 150A, 220A, 320A & 500A.

Equipped with advanced Micrologic trip unit which provides over-load and short circuit protection along with phase-unbalance or phase-loss protections.

Optional Thermal Fault module (SDTAM) to indicate over-load and to open contactor (before breaker tripping) in event of over-load or phase un-balance.

Suitable for 2 device motor-starter solutions along with TeSys contactors with Type 1 and Type 2 coordination.

Compliance with standards: EN/IEC 60947-1; IEC 60947-2; IEC 60947-4-1; UL 60947-4-1; CSA C22.2 No 60947-4-1.

Offer Marketing Illustration

Product benefits / Features



TeSys Giga Motor Circuit Breakers
Range Accessories

Long terminal shields

Direct rotary handle

Clip-on connectors

Phase barriers

Spreader

Kit for combination with contactor

The image displays a collection of accessories for TeSys Giga Motor Circuit Breakers. At the top left is a main circuit breaker unit. Below it, six categories of accessories are shown with their respective labels: Long terminal shields (black plastic covers), Direct rotary handle (a circular handle with a green indicator), Clip-on connectors (metal brackets), Phase barriers (black plastic sheets), Spreader (metal brackets), and Kit for combination with contactor (a metal assembly).