

Product datasheet

Specifications



13A 250V 1 Gang 3-Pin Universal Socket

KB413S

! Discontinued

Main

Range	Vivace
product or component type	Socket-outlet
Device short name	KB426
Device application	Power supply
device presentation	Complete mechanism
outlet standard	Universal
Colour tint	White
Type of packing	Plastic bag
Socket number	1
Rated current	13 A
Colour tint	Wall: white

Complementary

Integrated connection type	1 socket-outlet 220...250 V AC, maximum load current: 13 A
Outlet standard	Universal
Outlet poles configuration	2P + E with shutter
Number of gangs	1 gang
Material	Polycarbonate: grid plate Polycarbonate: surround Nylon: base
Projecting depth	8 mm
device mounting	Flush
mounting support	Wall mounted
Fixing mode	By screws
Fixing center	60.3 mm
Embedding depth	25 mm
Rated current	13 A at 250 V AC, resistive
[Ue] rated operational voltage	220...240 V
Network frequency	50/60 Hz
Network type	AC
Contacts material	Brass and phosphor bronze

Connections - terminals	Screw terminals
Terminal identifier	L N E
Tightening torque	0.4 N.m
Clamping connection capacity	2.5 mm ² 4 mm ²
Width	86 mm
Surface treatment	Untreated
Height	86 mm
Surface finish	Glossy
Depth	33 mm
Number of terminals	3
Clamping connection capacity	1 x 2.5...3 x 2.5 mm ² for rigid or stranded cable(s)

Environment

Ambient air temperature for operation	-5...40 °C
Ambient air temperature for storage	-5...60 °C
Relative humidity	0...95 %
Operating altitude	0...2000 m
Environmental characteristic	Indoor use
IP degree of protection	IP20

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.6 cm
Package 1 Width	3 cm
Package 1 Length	8.6 cm
Package 1 Weight	108.6 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	15 cm
Package 2 Width	19 cm
Package 2 Length	10 cm
Package 2 Weight	1.156 kg
Unit Type of Package 3	CAR
Number of Units in Package 3	100
Package 3 Height	21 cm
Package 3 Width	31.5 cm
Package 3 Length	50 cm
Package 3 Weight	11108 g

Contractual warranty

Warranty

18 months

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

Reach Free Of Svhc

Toxic Heavy Metal Free

Mercury Free

Rohs Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation

[REACH Declaration](#)

Eu Rohs Directive

Compliant

[EU RoHS Declaration](#)

China Rohs Regulation

[China RoHS declaration](#)

Pro-active China RoHS declaration (out of China RoHS legal scope)

Environmental Disclosure

[Product Environmental Profile](#)

Circularity Profile

No need of specific recycling operations