


# Bảng thông số sản phẩm

Thông số kỹ thuật



Earth-leakage add-on protection module, EasyPact CVS 100/160, 200VAC to 440VAC, 30mA to 10A, 4 poles

LV529489

## Main

Range of product	EasyPact CVS100...250
Range	EasyPact
Product or component type	Vigi add-on
Device application	Wiring
Range compatibility	EasyPact EasyPact CVS100 circuit breaker EasyPact EasyPact CVS160 circuit breaker
Poles description	4P
[In] rated current	100 A 160 A
Earth-leakage protection class	Class A Class AC
Residual earth-leakage sensitivity adjustment type	Adjustable
Earth-leakage sensitivity	0.03 A for class A 0.3 A for class A 1 A for class A 3 A for class A 10 A for class AC
Residual earth-leakage time delay adjustment type	Adjustable 4 settings
[Δt] residual earth-leakage time delay adjustment	0 ms 60 ms 150 ms 300 ms

## Complementary

Network type	AC
Network frequency	50/60 Hz
[Ue] rated operational voltage	200...440 V AC 50/60 Hz conforming to IEC 60947-2
Earth-leakage protection	With
Maximum breaking time	800 ms
Overvoltage category	II

## Environment

Electrical shock protection class	Class II
Standards	IEC 60947-2

## Packing Units

Unit Type of Package 1	PCE
------------------------	-----

<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	13.4 cm
<b>Package 1 Width</b>	14.2 cm
<b>Package 1 Length</b>	17.0 cm
<b>Package 1 Weight</b>	1.316 kg
<b>Unit Type of Package 2</b>	S03
<b>Number of Units in Package 2</b>	8
<b>Package 2 Height</b>	30 cm
<b>Package 2 Width</b>	30 cm
<b>Package 2 Length</b>	40 cm
<b>Package 2 Weight</b>	11.042 kg