

# Product datasheet

Specifications



## WPS - 20A 500V - 2 switched poles - IP66 (grey)

S56SW220GY

### Main

Range of product	WPS
product or component type	Isolating switch
Rated current	20 A at 500 V AC

### Complementary

device mounting	Surface
Switch function	2-way
poles description	2P
Number of gangs	1 gang
Material	PVC (polyvinyl chloride) UV stabilised
Height	107 mm
Width	101 mm
Depth	104 mm

### Environment

Environmental characteristic	Weatherproof
IP degree of protection	IP66
Motor M-rating AS3133	M150

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11.2 cm
Package 1 Width	10.5 cm
Package 1 Length	10.5 cm
Package 1 Weight	500.0 g

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

Mercury Free

Rohs Exemption Information Yes

## Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)  
Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure [Product Environmental Profile](#)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Circularity Profile No need of specific recycling operations