

Product datasheet

Specifications



WPS - 32A 500V - 3 switched poles - IP66 (grey)

S56SW332GY

Main

Range of product	WPS
product or component type	Isolating switch
Rated current	32 A at 500 V AC

Complementary

device mounting	Surface
Switch function	2-way
poles description	3P
Number of gangs	1 gang
Material	PVC (polyvinyl chloride) UV stabilised
Height	107 mm
Width	101 mm
Depth	104 mm

Environment

Environmental characteristic	Weatherproof
IP degree of protection	IP66
Motor M-rating AS3133	M180

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11.2 cm
Package 1 Width	10.5 cm
Package 1 Length	10.5 cm
Package 1 Weight	500.0 g

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

Mercury Free

RoHS Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu RoHS Directive Compliant with Exemptions

China RoHS Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile No need of specific recycling operations