





Main

| | |
|--|--|
| Range | Compact |
| Product or component type | Circuit breaker |
| Device short name | Compact NSX250N |
| Circuit breaker application | Distribution |
| Poles description | 4P |
| Protected poles description | 3t |
| Neutral position | Left |
| Network type | AC |
| Network frequency | 50/60 Hz |
| [In] rated current | 250 A (40 °C) |
| [Ui] rated insulation voltage | 800 V AC 50/60 Hz |
| [Uimp] rated impulse withstand voltage | 8 kV |
| [Ue] rated operational voltage | 690 V AC 50/60 Hz |
| Breaking capacity code | N |
| Breaking capacity | 15 kA at 600 V AC 50/60 Hz conforming to UL 508 Icu 90 kA at 220/240 V AC 50/60 Hz conforming to IEC 60947-2 Icu 50 kA at 440 V AC 50/60 Hz conforming to IEC 60947-2 Icu 50 kA at 380/415 V AC 50/60 Hz conforming to IEC 60947-2 Icu 36 kA at 500 V AC 50/60 Hz conforming to IEC 60947-2 90 kA at 240 V AC 50/60 Hz conforming to NEMA AB1 50 kA at 480 V AC 50/60 Hz conforming to UL 508 50 kA at 480 V AC 50/60 Hz conforming to NEMA AB1 20 kA at 600 V AC 50/60 Hz conforming to NEMA AB1 Icu 35 kA at 525 V AC 50/60 Hz conforming to IEC 60947-2 Icu 10 kA at 660/690 V AC 50/60 Hz conforming to IEC 60947-2 85 kA at 240 V AC 50/60 Hz conforming to UL 508 |
| [Ics] rated service breaking capacity | Ics 90 kA 220/240 V AC 50/60 Hz conforming to IEC 60947-2 Ics 50 kA 440 V AC 50/60 Hz conforming to IEC 60947-2 Ics 50 kA 380/415 V AC 50/60 Hz conforming to IEC 60947-2 Ics 36 kA 500 V AC 50/60 Hz conforming to IEC 60947-2 Ics 35 kA 525 V AC 50/60 Hz conforming to IEC 60947-2 Ics 10 kA 660/690 V AC 50/60 Hz conforming to IEC 60947-2 |
| Suitability for isolation | Yes conforming to IEC 60947-2 Yes conforming to EN 60947-2 |
| Utilisation category | Category A |
| Trip unit name | TM-D |
| Trip unit technology | Thermal-magnetic |
| Trip unit protection functions | LI |
| Trip unit rating | 200 A (40 °C) |
| Protection type | Overload protection (thermal) Short-circuit protection (magnetic) |
| Pollution degree | 3 conforming to IEC 60664-1 |

Complementary

| | |
|---|---|
| Control type | Toggle |
| Mounting mode | Fixed |
| Mounting support | Backplate |
| Upside connection | Front |
| Downside connection | Front |
| Mechanical durability | 20000 cycles |
| Electrical durability | 5000 cycles 690 V In conforming to IEC 60947-2 20000 cycles 440 V In/2 conforming to IEC 60947-2 10000 cycles 690 V In/2 conforming to IEC 60947-2 10000 cycles 440 V In conforming to IEC 60947-2 |
| Connection pitch | 35 mm |
| Local signalling | Positive contact indication |
| Neutral protection setting | No protection 3t |
| Long time pick-up adjustment type Ir | Adjustable |
| Long time pick-up adjustment range | 0.7...1 x In |
| Long time delay adjustment type | Fixed |
| [Tr] long-time delay adjustment | 15 s 6 x Ir 120...400 s 1.5 x In |
| Short-time pick-up adjustment type Isd | Adjustable |
| [Isd] short-time pick-up adjustment range | 5...10 x In |
| Short-time delay adjustment type | Fixed |
| Height | 161 mm |
| Width | 140 mm |
| Depth | 86 mm |
| Product weight | 2.8 kg |

Environment

| | |
|---------------------------------------|---|
| Electrical shock protection class | Class II |
| Standards | EN 60947-2 IEC 60947-2 NEMA AB1 UL 508 |
| Product certifications | CSA UL |
| IP degree of protection | IP40 conforming to IEC 60529 |
| IK degree of protection | IK07 conforming to IEC 62262 |
| Ambient air temperature for operation | -35...70 °C |
| Ambient air temperature for storage | -55...85 °C |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 0819 - Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold |
| Product environmental profile | Available |
| Product end of life instructions | Available Download End Of Life Manual |