



### Main

Range of product	Mureva Styl
Product or component type	Socket-outlet
Device presentation	Complete product
Outlet poles configuration	2P + E with shutters
Outlet standard description	Side earth
Outlet standard	Schuko
Colour tint	Grey (RAL 7016)

### Complementary

Device mounting	Surface
Rated current	16 A
Number of power socket outlets	2
[Ue] rated operational voltage	250 V AC
Condition of use	Indoor/outdoor
Material	Brass PC (polycarbonate) PP (polypropylene)
Fixing mode	By screws
Clamping connection capacity	1...2.5 mm <sup>2</sup> for rigid cable(s) 1...2.5 mm <sup>2</sup> for stranded cable(s) 1...2.5 mm <sup>2</sup> for flexible cable(s)
Wire stripping length	13 mm
Cable entry	Easy valve access diameter: 6...12 mm
Height	76 mm
Width	147 mm
Depth	64 mm

### Environment

Quality labels	AENOR EAC
IP degree of protection	IP55
IK degree of protection	IK08

Flame retardance	Self-extinguishing 650 °C conforming to IEC 60695-2-1
Ambient air temperature for operation	-5...40 °C
Ambient air temperature for storage	-25...55 °C

### Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)